


<b>Submittal Data: GAA12AA-D3RNA2C</b>		12,000 BTU/H Thru-The-Wall AIR CONDITIONER	
Job Name:	Location:	Date:	
Purchaser:	Engineer:		
Submitted to:	For: <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction		
Unit Designation:	Schedule No.:		
<b>GENERAL FEATURES:</b> -Cooling and Heating , also with Electric Heater -R-410a Refrigerant -Compact and Quiet Design -3D Airflow -Auto Restart Function -Wireless Remote with LCD Display - 3 Speed-Fan - Comfortable Sleep Mode			
System Ratings		Indoor Side Data	
<b>Ratings</b> Rated Cooling Capacity 11,500-11,700 BTU/H Power Input (Cooling) 1,200-1,220 W Power Current (Cooling) 5.6 / 6.1 A EER 9.6 Rated Heating Capacity 11,200-11,400 BTU/H Power Input (Heating) 1,140-1,160 W Power Current (Heating) 5.4 / 5.9 A COP 9.9		<b>Fan Motor</b> Output Power 30 W RLA 0.33 A <b>Airflow</b> Air Flow Volume (L/M/H) 224/247/271 CFM  <b>Sound Level</b> Sound Pressure Level (L/M/H) 55/57/59 dB (A) Sound Power Level (L/M/H) 65/67/69 dB (A)	
<b>Compressor</b> Type Rotary RLA 5.2 A Power Input 1135 W		Outdoor Side Data	
<b>Unit Dimensions/Weight</b> Dimensions 26 x 15-5/8 x 21-1/6-in 660 x 397 x 538 mm Net Weight 86 lbs. 39 kg		<b>Fan Motor</b> Output Power 65 W FLA 0.6 A <b>Airflow</b> Air Flow Volume 530 CFM <b>Sound Level</b> Sound Pressure Level 69 dB (A) Sound Power Level 79 dB (A)  <b>Moisture Protection</b> IP24	
<b>Operating Range</b> Cooling (Max) (43 °C) (Min) (18°C)		<b>Refrigerant Piping Data</b> Evaporator Pipe Diameter 2/7-inch Condenser Pipe Diameter 1/5+2/7-inch	
<b>Power Supply</b> Normal Operational Voltage 208-230 V, 1 Phase, 60 Hz			



