


Submittal Data: GAA09AA-D3RNA2C		9,000 BTU/H Thru-The-Wall AIR CONDITIONER	
Job Name:	Location:	Date:	
Purchaser:	Engineer:		
Submitted to:	For: <input type="checkbox"/> Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction		
Unit Designation:	Schedule No.:		
GENERAL FEATURES: -Cooling and Heating , also with Electric Heater -R-410a Refrigerant -Compact and Quiet Design -3D Airflow -Auto Restart Function -Wireless Remote with LCD Display - 3 Speed-Fan - Comfortable Sleep Mode			
System Ratings		Indoor Side Data	
Ratings Rated Cooling Capacity 9,100-9,300 BTU/H Power Input (Cooling) 940/960 W Power Current (Cooling) 4.4 / 4.8 A EER 9.7 Rated Heating Capacity 8,600-8,800 BTU/H Power Input (Heating) 840 / 860 W Power Current (Heating) 4.0 / 4.3 A COP 10.2		Fan Motor Output Power 30 W RLA 0.33 A Airflow Air Flow Volume (L/M/H) 224/247/271 CFM Sound Level Sound Pressure Level (L/M/H) 55/57/59 dB (A) Sound Power Level (L/M/H) 65/67/69 dB (A)	
Compressor Type Rotary RLA 3.8 A Power Input 830 W		Outdoor Side Data	
Unit Dimensions/Weight Dimensions 26 x 15-5/8 x 21-1/6-in 660 x 397 x 538 mm Net Weight 83 lbs. 37.5 kg		Fan Motor Output Power 65 W FLA 0.6 A Airflow Air Flow Volume 530 CFM Sound Level Sound Pressure Level 69 dB (A) Sound Power Level 79 dB (A) Moisture Protection IP24	
Operating Range Cooling (Max) (43 °C) (Min) (18°C)		Refrigerant Piping Data Evaporator Pipe Diameter 2/7-inch Condenser Pipe Diameter 1/5+2/7-inch	
Power Supply Normal Operational Voltage 208-230 V, 1 Phase, 60 Hz			



